

# 南亞 PVC 膠粒 UL 認證規格表

UL QMFZ2.E98658

PLASTICS-COMPONENT

Material Designation	COLOR	MIN THK	FLAME CLASS	HWI	HAI	RTI			適用製品
						ELEC	MECH		
							IMP	STR	
3M7B000BUX	WT	1.3	V-0	—	—	50	50	50	射出配件
	NC,RD,BK	1.3	V-0,5VA	—	—	50	50	50	
	ALL	1.5	V-0,5VA	—	—	50	50	50	
	ALL	3.0	V-0,5VA	—	—	50	50	50	
3M7C000BXX	ALL	2.0	V-0	—	—	50	50	50	射出配件
		3.6	V-0	—	—	50	50	50	
3MPK000AUA	ALL	1.5	V-0	—	—	50	50	50	配線槽
		3.0	V-0	—	—	50	50	50	
3MPK000AUB	ALL	1.5	V-0	—	—	50	50	50	配線槽
		3.0	V-0	—	—	50	50	50	
3MPW006ALX(V)	ALL	0.6	V-0	2	0	50	50	50	押出端子
		3.0	V-0	1	0	50	50	50	
3MQA000AXA0F0	WT	1.5	V-0	—	—	50	50	50	射出配件
		3.0	V-0	—	—	50	50	50	
3MQA000VXX0F1	ALL	1.4~1.6	V-0	—	—	50	50	50	射出配件
				—	—	50	50	50	
3MSB062FUX	ALL	1.5	V-0	—	—	50	50	50	抗氧化線
		3.0	V-0	—	—	50	50	50	
3MST041FUX	ALL	1.5	V-0	—	—	50	50	50	汽車花線
		3.0	V-0	—	—	50	50	50	
3MTA004AGA	ALL	1.5	V-0	—	—	50	50	50	醫材射出配件
		3.0	V-0	—	—	50	50	50	
3MTG035FUX	ALL	1.5	V-0	—	—	50	50	50	插頭
		3.0	V-0	—	—	50	50	50	

NOTES : (V) -Vicat softening point is 89 degree C °

QMTT2.E219607

Polymeric Materials for Use in Wire, Cable and Flexible Lighting Products Component

Grade Dsg	Color	INS	JKT	Temp Rating (°C)	Oil Resistance Rating/Standard
3MSG048UKC	All(except clear)	-	X	105	-